



Electric wire rope hoists T81 Conveying one with a crane trolley, reeving 2/1

- (1) with micro-lifting
- (2) with load limitation
- (3) with load limitation and with micro-lifting

Type	Reeving 2/1		Dimensions, mm																							
	Lifting height, m	Lifting capacity, kg	Lifting speed m/min				L2	L3	L4	L5	L6	L7	L8	H1	H2	B	B1	B2	B3	B4	B5	B6	B7	e	C	D
			8	12	8/2	12/2																				
T813...	H1	6	709	749	310	365	48	55	565	750	70	470	43... 58	1000	465 492 ⁽¹⁾ 557 ⁽³⁾	300 365 ⁽²⁾	200	40	455... 510	50	50	18	500	160		
	H2	9	814	854	362	470	75	82	670	855																
	H3	12	914	954	412	570	100	106	770	955																
	H4	18	1114	1154	512	770	75	231	970	1155																
	H5	24	1314	1354	612	970	149	332	1170	1355																
	H6	30	1426	1490	667	1004	90	312	1004	1189																
	H7	36	1526	1593	712	1094	110	338	1294	1479																
T814...	H1	6	816	880	362	394	45	51	594	779	80	562	43... 58	1000	580 606 ⁽¹⁾ 668 ⁽³⁾	380 442 ⁽²⁾	270	45	455... 510	50	50	22	550	160		
	H2	9	926	990	417	504	73	79	704	889																
	H3	12	1026	1090	467	604	96	104	804	989																
	H4	18	1226	1290	567	804	90	212	1004	1189																
	H5	24	1426	1490	667	1004	90	312	1204	1389																
	H6	30	1535	1623	710	1070	88	346	1270	1455																
	H7	36	1640	1728	762	1175	75	398	1375	1560																
T815...	H1	6	856	923	377	424	52	59	624	809	80	562	43... 58	1000	580 606 ⁽¹⁾ 668 ⁽³⁾	380 442 ⁽²⁾	270	50	455... 510	50	50	22	650	160		
	H2	9	976	1043	437	544	82	89	744	929																
	H3	12	1086	1153	492	654	110	116	854	1039																
	H4	18	1306	1373	602	874	110	226	1074	1259																
	H5	24	1526	1593	712	1094	110	336	1294	1479																
	H6	30	1640	1728	762	1175	75	398	1375	1560																
	H7	36	1815	1903	850	1350	75	436	1550	1375																
T816...	H1	6	905	993	395	440	49	66	640	825	90	657	43... 58	1000	675 682 ⁽¹⁾ 760 ⁽³⁾	430 508 ⁽²⁾	330	56	455... 510	50	50	26	730	160		
	H2	9	1010	1098	448	545	75	82	745	930																
	H3	12	1115	1203	500	650	101	108	850	1035																
	H4	18	1325	1413	605	860	124	193	1060	1245																

